

# Using Locality for Efficient Query Evaluation in Various Computation Models

Nicole Schweikardt

Department of Computer Science  
Humboldt-Universität zu Berlin  
schweikn@informatik.hu-berlin.de

---

## Abstract

In the database theory and logic literature, different notions of *locality* of queries have been studied, the most prominent being Hanf locality [6, 4, 12] and Gaifman locality [5, 8]. These notions are designed so that, in order to evaluate a local query in a given database, it suffices to look only at small neighbourhoods around tuples of elements that belong to the database.

In this talk I want to give a survey of how to use locality for efficient query evaluation in various computation models. In particular, we will take a closer look at how to enumerate query results with constant delay [2, 9, 3], and at how to evaluate queries in a map-reduce like setting [11] or in Pregel [10]. Also, we will have a closer look at how to transform a given local query into a form suitable for exploiting its locality [1, 7].

**1998 ACM Subject Classification** H.2.4 [Database Management]: Systems – *Query Processing*, H.2.3 [Database Management]: Languages – *Query Languages*, F.4.1 [Mathematical Logic and Formal Languages]: Mathematical Logic – *Computational Logic, Model Theory*

**Keywords and phrases** query evaluation, locality

**Digital Object Identifier** 10.4230/LIPIcs.ICDT.2015.13

**Category** Invited Talk

---

## References

- 1 B. Bollig and D. Kuske. An optimal construction of Hanf sentences. *J. Applied Logic*, 10(2):179–186, 2012.
- 2 A. Durand and E. Grandjean. First-order queries on structures of bounded degree are computable with constant delay. *ACM Trans. Comput. Log.*, 8(4), 2007.
- 3 A. Durand, N. Schweikardt, and L. Segoufin. Enumerating answers to first-order queries over databases of low degree. *Proc. PODS 2014*, pages 121–131, 2014.
- 4 R. Fagin, L. Stockmeyer, and M. Vardi. On Monadic NP vs Monadic co-NP. *Inf. Comput.*, 120(1):78–92, 1995.
- 5 H. Gaifman. On local and nonlocal properties. In J. Stern, editor, *Logic Colloquium’81*, pages 105–135. North-Holland, 1982.
- 6 W. Hanf. Model-theoretic methods in the study of elementary logic. In *The Theory of Models*, J. Addison, L. Henkin, and A. Tarski, Eds. North Holland, 1965, pp. 132–145.
- 7 L. Heimberg, D. Kuske, and N. Schweikardt. An Optimal Gaifman Normal Form Construction for Structures of Bounded Degree. *Proc. LICS 2013*, pages 63–72, 2013.
- 8 L. Hella, L. Libkin, and J. Nurmonen. Notions of locality and their logical characterizations over finite models. *J. Symb. Log.*, 64(4):1751–1773, 1999.
- 9 W. Kazana and L. Segoufin. First-order query evaluation on structures of bounded degree. *Logical Methods in Computer Science*, 7(2), 2011.



© Nicole Schweikardt;  
licensed under Creative Commons License CC-BY  
18th International Conference on Database Theory (ICDT’15).

Editors: Marcelo Arenas and Martín Ugarte; pp. 13–14



Leibniz International Proceedings in Informatics

LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

- 10 G. Malewicz, M. Austern, A. Bik, J. Dehnert, I. Horn, N. Leiser, G. Czajkowski Pregel: a system for large-scale graph processing. *Proc. SIGMOD 2010*, pages 135–146, 2010.
- 11 F. Neven, N. Schweikardt, F. Servais, and T. Tan. Distributed Streaming with Finite Memory. *Proc. ICDT 2015*.
- 12 J. Nurmonen. Counting Modulo Quantifiers on Finite Structures. *Inf. Comput.*, 160(1–2):62–87, 2000.